

## D795WT

Extreme Short-Throw Advantages  
with Crossover Possibilities



## D795WT

### Extreme Short-Throw Advantages with Crossover Possibilities

The Vivitek D795WT WXGA crossover projector can create a 93" image from about 1.3' away. This extreme short-throw projector features 3000 lumens of brightness, a 2500:1 contrast ratio, DLP® and BrilliantColor™ technologies for impressive color reproduction and amazing picture performance. With its assortment of connectivity options and a built-in speaker, the D795WT is the ultimate solution for the latest multimedia and widescreen needs.

### Features:

- 3000 lumens of brightness with a 2500:1 contrast ratio
- DLP® and BrilliantColor™ technologies from Texas Instruments
- 3D-ready
- Connectivity options include: HDMI v1.3, two (2) VGA-in, composite video, S-video
- VividWheel III for improved color reproduction and automatic gain control
- Top-loading, cover for quick and easy lamp replacement

<b>Brightness</b>	3000 Lumens (Typical)
<b>Native Resolution</b>	WXGA (1280 x 800)
<b>Max. Resolution</b>	UXGA (1600 x 1200)
<b>Contrast Ratio</b>	2500:1 (Full On/Off)
<b>Lamp Life and Type</b>	≈4000/6000Hours ( Boost/Standard Mode), 220W
<b>Lamp Part #</b>	TBA
<b>Display Type</b>	Single DMD DLP® Technology by TexasInstruments
<b>Throw Ratio</b>	0.19:1 (Distance/Width)
<b>Image Size (Diagonal)</b>	86.7" to 97" (2.2 to 2.4 m)
<b>Projection Distance</b>	22.4 ± 10 mm to 62.3 ± 10 mm (0.88" ± 0.4" to 2.45" ± 0.4")
<b>Projection Lens</b>	F=2.4, Manual Focus
<b>Aspect Ratio</b>	16:10 Native, 16:9 & 4:3 Compatible
<b>Keystone Correction</b>	±15° Vertical
<b>Color Spectrum</b>	16.7 Million
<b>Horizontal Scan Rate</b>	15, 30 to 90 KHz
<b>Vertical Scan Rate</b>	43 to 85 Hz

<b>Speaker</b>	10W Mono
<b>Remote Control</b>	Fully Featured IR Remote with Laser Pointer and Mouse
<b>Projection Method</b>	Table Top or Ceiling Mount (Front or Rear)
<b>Uniformity</b>	85%
<b>Computer Compatibility</b>	UXGA, SXGA+, SXGA, XGA, SVGA, VGA Resized; VESA Standards; PC and Macintosh Compatible
<b>Video Compatibility</b>	SDTV(480i), EDTV(480p), HDTV (576i/p, 720p, 1080i/p), NTSC/NTSC 4.43, PAL B/G/H/I/M/N 60, SECAM
<b>I/O Connection Ports</b>	HDMI v1.3, VGA-In (x2), Composite Video, S-Video, RCA Audio-In, Mini-Jack Audio-In
<b>Security</b>	Kensington® Lock Port, Security Bar
<b>Weight</b>	19.84 lbs (9.0 kg)
<b>Dimensions (W x H x D)</b>	13.94"x 8.62" x 16.16" (354 x 219 x 410.5 mm)
<b>Noise Level</b>	27dB/29dB (Standard/ Boost Mode)
<b>Power</b>	Supply: AC 100-240V, 50/60Hz Consumption: 290W (Boost Mode), 240W (Standard Mode), <1W (Standby Mode)
<b>Operating Temperature</b>	41 to 104°F (5 to 40°C)
<b>Warranty</b>	1-Year Limited Warranty, 90-Day Lamp Warranty
<b>Standard Accessories</b>	AC Power Cord, VGA Cable, Remote Control, Batteries for Remote, User Manual (CD), Warranty Card
<b>Optional Accessories</b>	Replacement Lamp, Remote
<b>UPC</b>	8 14964 33524 1

**Please Note:** Product Specification subject to change without prior notice.



Suite 401 | Jumeirah Terrace,  
 Jumeirah 1, PO Box 118821,  
 Dubai, U.A.E.  
 E-mail :: [info@granteq.com](mailto:info@granteq.com)

Telephone :: +971 4 3464646  
 FAX :: +971 4 3464647  
 Vid Conf :: +971 4 3464641  
 Web: [www.granteq.com](http://www.granteq.com)